



AXRO FQC2 M

ELASTIC BINDER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING


The Cyklop Axro FQC2 M is a well-known elastic binder, constructed in stainless steel. That makes it very suited for working in humid areas such as in the food industry. This machine is fitted with the AXRO clamping and knotting technology which has more than proven its reliability over the years. The AXRO-FQC2 is fitted with an updated "feed-in" mechanism whereby products are still bound properly even in the event of premature bind timing. This unit is also equipped with a knot-release system which controls the release of the knot. This results in minimal pulling to the product and prevents it from incurring any damage. The binder is suitable for manually bundling products such as flowers, vegetables, cables, and many other products.

Advantages

- For elastic cord Cylastic PES, Cylastic PCs 1300, Cylastic 3K
- Can be integrated into automatic machine lines
- Extremely easy operation
- Robust, capable of continuous operation
- Minimal maintenance
- Low noise
- Up to 100 cycles/minute
- Stainless Steel: suitable for wet conditions



[< CLICK HERE FOR A VIDEO OF THE FQC2 M >](#)



Technical data	
Speed	Up to 100 cycles/minute
Dimensions (HxWxD)	780 x 495 x 418 mm
Transit depth (HxD)	150 x 250* mm * 350 or 600 mm optional
Input	Left (standard), right optional
Start switch	Tabletop* * Upper switch or photocel optional
String tension	Adjustable up to 110 N
Consumables	Cylastic PES, PCs 1300, 3K
Power supply	200-240 V / 50-60 Hz / 1 phase 100-120 V / 50-60 Hz / 1 phase
Weight	47 kg
Noise	Max. 5,7 dB

S.A. Cyklop Belgium N.V.
Boulevard International 55 C3
1070 Brussels

+32 2 7260080
www.cyklop.be
info@cyklop.be

