



CR 19

STEEL STRAPPING TOOL

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The CR 19 is a robust battery driven steel strapping tool and is suitable for 13, 16 and 19 mm steel strap. The CR 19 can be used for both horizontal and vertical straps, making the device efficient to use. Manual tensioning and closing of steel strap with seals require minimal effort with this model tensioner.

Advantages

- For steel strap 13, 16, 19 mm
- Horizontal and vertical strapping
- Robust, for heavy applications
- Tensions up to 3,000 N

Options

- Protective cover display
- Bottom protection plate
- Suspension bracket for stationary use



Technical specifications	
Weight	4.5 kg
Dimensions (LxWxH)	390 x 150 x 140 mm
Sealing method	Sealjoint with single notch
Tension	400 - 3,000 N
Tension speed	135 mm/s
Seal efficiency	approx. 55% of strap tensile strength
Operating temperature	-10 °C to +40 °C
Battery	Bosch Li-Ion ProCORE 18 V 4.0 Ah
Power supply	100 / 110 / 230 V
Charging time	50 min.
Strapping / battery	Up to 500
Strapping material	Steel strap
Dimensions strapwidth / thickness	19 mm / 0,80 mm

Cyklop International
 Industriestraße 133, D-50996 Köln
 (Rodenkirchen)
 Postfach / P.O. Box 50 12 20,
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

